

# Dick Anderson Construction Safety Orientation Test

**2017**

Employer (Print): \_\_\_\_\_

Name (Print): \_\_\_\_\_

Date: \_\_\_\_\_

1. Who is authorized and expected to stop an unsafe act or unsafe condition?
  - a. Superintendents
  - b. Co-worker
  - c. Yourself
  - d. All of above
2. All subcontractors on DAC projects are required to wear- durable long pants, t-shirt w/ standard 4" sleeve and\_\_\_\_\_?
  - a. Hard hat, safety glasses, reflective vest or Hi-Viz shirt, and safety toed boots
  - b. Hard hat and gloves
  - c. Safety Toed boots and safety glasses
  - d. Respirator, head lamp, and goggles
3. What is the main purpose of a Job Hazard Analysis (JHA)/Job Safety Analysis (JSA)?
  - a. Create more paperwork
  - b. Step by step of the work process, identifying the hazards and preventive measures
  - c. Creating hazards and eliminating preventive measures
  - d. Step by step of task and corrective actions for hazards
4. How often must you clean your work area?
  - a. Weekly
  - b. Monthly
  - c. Minimum daily, but more often if needed
  - d. Bi-weekly
5. What is the proper inspection process for scaffolding?
  - a. The complete system must be inspected prior to use and tagged with a green tag if ok to use
  - b. The complete system must be inspected prior to use and tagged with a yellow tag if ok to use with fall protection
  - c. The complete system must be inspected prior to use and tagged with a red tag if not approved for access
  - d. All of above
6. Fall protection anchorages must be able to support how many pounds per employee?
  - a. 250 lbs
  - b. 5000 lbs
  - c. 500 lbs
  - d. 1000 lbs

7. Ladders must be inspected prior to use, properly set up, secured and must extend \_\_\_\_ feet past the landing
  - a. 3'
  - b. 1'
  - c. 18"
  - d. 24"
8. What is the proper height for a standard guardrail/handrail?
  - a. 36" for top rail, 21" for mid rail and 4" toe board
  - b. 42" plus/minus 3" for top rail, 21" for mid rail and 4" toe board
  - c. 42" for top rail, 18" for mid rail and 4" toe board
  - d. No requirement height
9. Subcontractor can only use DAC equipment after written approval and proper insurance verification?
  - a. True
  - b. False
10. Damaged power tools, cords and connectors must be \_\_\_\_\_?
  - a. Red tagged and removed from job immediately
  - b. Throw away
  - c. Red tagged, properly repaired and re-inspected prior to use
  - d. A or C
11. Prior to working on DAC projects you must \_\_\_\_\_?
  - a. Have proper authorization to be on site
  - b. Check in with Superintendent for all site rules
  - c. Have completed orientation video
  - d. All of above
12. Failure to perform work in a safe manner may lead to disciplinary action?
  - a. True
  - b. False
13. All workers performing tasks involving respirable silica must follow Table I Exposure Controls set by OSHA?
  - a. True
  - b. False
14. Why do you work safe \_\_\_\_\_?

I hereby acknowledge that I have received, viewed, comprehended and successfully completed the Dick Anderson Construction safety policies, orientation video, and related test. I understand that Dick Anderson Construction reserves the right to make changes and interpretations, in its sole judgment, to company policies and procedures with or without notice. I agree to comply with these Dick Anderson Construction policies and procedures, and I understand the consequences of my failure to comply with such policies may result in disciplinary action up to and including removal from a work site.

Signature \_\_\_\_\_ Date: \_\_\_\_\_

Dick Anderson Construction Supervisor \_\_\_\_\_ Date: \_\_\_\_\_